

WP-15

TECHNICAL DATA SHEET

Water Washable Penetrant - red



EXCLUSIVE EDITION BY

MR CHEMIE
NDT-MATERIALS



Product Characteristics

- Penetrant - Visible for penetrant testing acc. to EN ISO 3452:2
 - Low in Sulphur & Halogen Content
 - Carrier medium - Oil
 - Easy Removable from the Surface using Water
 - Bright Red Indications
 - Excellent Capillary Action
- Good Surface Wetting
Toluene Free

Minimum shelf life / Temperatures



Aerosol / Bulk:
3 years at storage temperature
Storage: +5°C - +45°C
Application: -10°C to +50°C (Dye Penetrant Testing)

Approvals / Specification



AMS 2644 / (DIN) EN ISO 3452-2 /
(DIN) EN ISO 3452-6 / JIS 2343-2 /
ASME Code V, Art. 6 / ASTM E1417 /
ASTM D516/09-11 / ASTM E165/E165M /
TLV 9017 01:2011-01 / PMUC / RCC-M / **NPCIL**
RDSO-M&C/NDT/105/2001 / IS3658 / IS12889

Further Information

Process description according to 3452-1 on request. For additional information refer material safety data sheet.

Suggested Product Family

Pre-cleaner: SC-20
Penetrant: SP-10 or WP-15
Remover: SC-20
Developer: SD-30

Packaging & Order Instructions

SKU	Pack Size	Case
2511-0143	Aerosol - 400ml	20
2511-0144	Bulk - 1L	6
2511-0145	Bulk - 5L	-

technical changes reserved!

ALL STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON VALIDATIONS AND TEST CONDUCTED BY 3AK CHEMIE OR ITS PARTNERS AND ARE BELIEVED TO BE RELIABLE, BUT THE ACCURACY OR COMPLETENESS THEREOF IS NOT GUARANTEED. THIS DATA SHEET AND INFORMATION IT CONTAINED HEREIN IS CONSIDERED TO BE ACCURATE AT THE DATE OF PRINTING. IT IS USER'S OBLIGATION TO EVALUATE AND USE PRODUCTS SAFELY AND WITHIN THE SCOPE ADVISED IN THE DATA SHEET AND TO COMPLY WITH ALL APPLICABLE LAWS AND REGULATIONS. BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMED ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION HEREWITH. *ALWAYS TEST APPLY ON A SMALL HIDDEN PORTION OF THE SUBSTRATE BEFORE APPLYING.